

# Acczent Unik



THE BUILT-IN ANTIMICROBIAL PROTECTION



Acczent Unik is designed for loose laying but can also be bonded. Loose laying has practical and financial benefits in many situations. In most cases Acczent Unik can be laid onto the existing floor. The surface is reinforced with polyurethane, sealing it and making it easy to clean. Acczent Unik is Sanitized®, (PUR) Topclean, bacteriostatic and fungistatic built in treatment.

Technical data	Test method	ACCZENT UNIK
Type of floor covering	EN 649	Compact heterogeneous vinyl flooring. Glass fibre reinforced, with polyester on the backing
Classification	EN 685	Domestic: 23. Commercial: 34. Industrial: 42
Wear layer thickness	EN 429	0.70 mm
Polyurethane (PUR) Topclean reinforced		Yes
Total thickness	EN 428	2.0 mm
Weight/m <sup>2</sup>	EN 430	3,060 g/m <sup>2</sup>
Abrasion/thickness loss	EN 660-1	≤ 0.08 mm (Group T)
Residual indentation	EN 433	≤ 0.10 mm
Castor chair	EN 425	Approved (applies to bonded product)*
Thermal conductivity	DIN 52612	0.02 m <sup>2</sup> K/W
Underfloor heating		Approved
Electrical resistance	EN 1081	ca 1 x 10 <sup>10</sup> Ohms
Impact sound absorption	NF En ISO 140-8	Δ Lw = 4 dB
Flame spread	DIN 4102	B1
	per EN ISO 9239-1	Bfl S1
Colour fastness	EN ISO 105-B02	≥ 6
Chemical resistance	EN 423	Good
Slip resistance	ZH 1/571 DIN 51130	R10
Colours		8
Form of delivery	EN 426	Sheet (rolls) 23 x 2 m
Dimensional stability	EN 434	≤ 0.10%

\* For loose laying, chair protection such as sheets of plexiglass must be used under office chairs with wheels.

#### Pattern matching

Colour ref.	L/W (cm)	Reverse laying
H212 Solo	0/0	Yes
H179 Provence	0/0	Yes
H216 Oak	Displaced trans-versed joint/7.7	No
H217 Beech	Displaced trans-versed joint/7.7	No

Follow Tarkett Sommer's installation and care instructions carefully. Bear in mind that choice of colour will affect the maintenance of the flooring and the frequency of cleaning. Variations in colour between samples and delivered goods may occur. We reserve the right to make any changes.

April 2000

**Australia:** Tarkett Sommer Pty Ltd – Tel. 61 2 96 34 73 73 • **Austria:** Tarkett Sommer Ges.m.b.H – Tel. 43 1 47 88 062 • **Belgium:** s.a. Tarkett Sommer n.v. – Tel. 32 2 520 04 67 • **Canada:** Domco Tarkett Inc. – Tel. 1 450 293 3173 • **Central & Eastern Europe:** Tarkett Sommer SA – Tel. 420 2 231 83 23 • **Czech Republic:** Tarkett Sommer Prague – Tel. + 420 2 231 8323 • **Denmark:** Tarkett Sommer A/S – Tel. +45 43 90 60 11 • **Finland:** Tarkett Sommer Oy – Tel. 358 9 682 31 20 • **France:** Tarkett Sommer SA – Tel. 33 1 41 20 41 20 • **Germany:** Tarkett Sommer Vertriebs GmbH & Co KG, Bereich Objekt – Tel. +49 6233 810 • **Greece:** Tarkett Sommer Monoprosopi Ltd – Tel. 30 1 5763889 • **Hong Kong:** Tarkett Sommer Asia Pacific Ltd. – Tel. 852 2511 8716 • **Italy:** Tarkett Sommer S.p.A. – Tel. 39 02 319 211 • **Mexico:** Tarkett Sommer – Tel. 52 5 651 25 94/99 • **Middle East:** Tarkett Sommer Middle East – Tel. 961 1 75 2363/4 • **Netherlands:** Tarkett Sommer Benelux BV – Tel. 31 0346 260 260 • **Norway:** Tarkett Sommer AS – Tel. 47 32 20 92 00 • **Poland:** Tarkett Sommer Polska Sp. z o.o – Tel. +48 22 833 10 97/+48 22 639 30 25 • **Portugal:** Tarkett Sommer SA – Tel. 351 21 756 75 40 • **Romania:** Tarkett Sommer Bucharest – Tel. 401 222 23 55 • **Russian Federation:** Sommer Russia – Tel. 7 095 937 74 50/51 • **Singapore:** Tarkett Sommer Far East – Tel. 65 743 53 84 • **Spain:** Tarkett Sommer SA – Tel. 34 91 358 00 35 • **Sweden:** Tarkett Sommer Försäljnings AB – Tel. 46 8 625 19 00 • **Switzerland:** Tarkett Sommer GmbH – Tel. 41 62 737 90 50 • **United Kingdom:** Tarkett Sommer Ltd – Tel. +44 (0)1905 342700 • **United States:** Domco Tarkett Inc. USA – Tel. 1 610 266 5500

<http://www.tarkett-sommer.com>



**Tarkett Sommer**




## Compact Resilient Commercial Floorcovering



# Acczent Unik

For loose laying in public spaces



**Tarkett Sommer**



## For loose laying in public spaces

Acczent Unik is a heterogeneous vinyl flooring specially developed for loose laying and adapted to the tough demands of public spaces. It's easy to create beautiful matching interiors with 8 co-ordinated colours and patterns to choose from. Acczent Unik is available in 3 single colours, 2 wood-effect patterns and 3 patterns from the Solo series.

With its polyurethane reinforced wear layer, Acczent Unik has the same great wear resistance as Acczent.

The difference is that Acczent Unik can be loose laid. This is where its extremely high shape and dimensional stability comes into its own.



# Acczent Unik

There are several advantages to loose laying. Loose laying hides minor irregularities in the subfloor. Subfloor work is easier and the time-consuming work of preparing the underlay does not need to be repeated at a later date.



## Great for the environ- ment and your pocket

Our loose laying system is the result of our approach to and work on total economy and the environment.

When refurbishing, the job of ripping out the old bonded flooring is tough and demanding. With a loose laid floor the old floor can just be lifted out.

Loose laying saves time and money as faster and simpler installation reduces the amount of time for which the area has to be out of use. You also save the cost of adhesive and adhesive application.



## Recycling

Production is not the only stage at which we take the environment into consideration. It is also uppermost in our minds during installation when a large amount of waste material is generated. The waste is collected up and sent to the recycling plant in Ronneby, Sweden.



CD179S  
Welding rod No. R5510-M




CD179T  
Welding rod No. R5511-M



CD179D  
Welding rod No. R5512-M



CC212D  
Welding rod No. R5502-M



CC212S  
Welding rod No. R5500-M



CC212W  
Welding rod No. 0399-M



CD216T  
Welding rod No. R5507-M



CD217T  
Welding rod No. R5516-M

Due to the limitations of the printing technology, the floor colours pictured may differ slightly from the actual colours. We reserve the right to make any changes.