

A standard quality flooring that meets your expectations

Somplan 50/150 is a range of homogeneous flooring whose harmonious colours create a light, airy ambience. The acrylic-based pore seal gives a simpler initial polish treatment and a more resistant wearlayer during building work. This flooring offers new options when your budget is limited and you want a standard quality flooring that meets your expectations.







Somplan 50/150 is a multi-purpose flooring recommended for use in apartments, smaller retail outlets, offices, lounges and retirement homes.












SOMPLAN 150 (2.0 mm)

 AL 860120 sheet AD 860160 tiles NCS 1500-N Welding Rod No. R5203-M	 AL 860520 sheet AD 860560 tiles NCS 2010-Y20R Welding Rod No. R4373-M	 AL 860820 sheet AD 860860 tiles NCS 2010-R60B Welding Rod No. R5200-M
 AL 860220 sheet AD 860260 tiles NCS 2500-N Welding Rod No. R5201-M	 AL 860620 sheet AD 860660 tiles NCS 2030-Y40R Welding Rod No. R5204-M	 AL 860920 sheet AD 860960 tiles NCS 3020-R90B Welding Rod No. R4370-M
 AL 860320 sheet AD 860360 tiles NCS 3502-B Welding Rod No. 0208-M	 AL 860720 sheet AD 860760 tiles NCS 2020-Y30R Welding Rod No. R2158-M	 AL 861020 sheet AD 861060 tiles NCS 3010-G20Y Welding Rod No. R5202-M
 AL 860420 sheet AD 860460 tiles NCS 2005-Y40R Welding Rod No. 0192-M		

SOMPLAN 50 (1.5 mm)

 AL 850125 sheet AD 850130 tiles NCS 1500-N Welding Rod No. R5203-M	 AL 850425 sheet AD 850430 tiles NCS 2005-Y40R Welding Rod No. 0192-M	 AL 850925 sheet AD 850930 tiles NCS 3020-R90B Welding Rod No. R4370-M
 AL 850325 sheet AD 850330 tiles NCS 3502-B Welding Rod No. 0208-M	 AL 850525 sheet AD 850530 tiles NCS 2010-Y20R Welding Rod No. R4373-M	 AL 851025 sheet AD 851030 tiles NCS 3010-G20Y Welding Rod No. R5202-M

Please note that the printed colours of the product shown may differ from reality.

SOMPLAN 50/150

Somplan 50/150 are homogeneous vinyl floor coverings suitable for use in commercial areas. Available in sheet and tile form.

Technical data	SOMPLAN 50	SOMPLAN 150
Type of floor covering	EN 649 Homogeneous vinyl flooring	Homogeneous vinyl flooring
Classification	EN 685 Commercial: 32 Industrial: 41	Commercial: 34 Industrial: 43
Surface treatment	factory seal	factory seal
Total thickness	EN 428 1.5 mm	2.0 mm
Weight/m ²	EN 430 2.7 kg	3.6 kg
Dimensional stability	EN 434 ≤ 0.40 %	≤ 0.40 %
Abrasion resistance	EN 660: Part 1 EN 660: Part 2 Group M: ≤ 0.30 mm Group M: ≤ 7.5 mm ³	Group M: ≤ 0.30 mm Group M: ≤ 7.5 mm ³
Residual indentation	EN 433 approx. 0.06 mm	approx. 0.06 mm
Wear by chair castors	EN 425 suitable	suitable
Flexibility	EN 435 OK	OK
Electrical resistance	EN 1081 approx. 10 ¹⁰ Ohm	approx. 10 ¹⁰ Ohm
Thermal resistance	DIN 52612 0.01 m ² K/W	0.01 m ² K/W
Fire test	DIN 4102 BS 476: Part 7, 1997 prEN 13501-1 prEN ISO 9239-1 B1 – Class B ₁ s1 ≥ 8 kw/m ²	B1 Class 2Y Class B ₁ s1 ≥ 8 kw/m ²
Colour fastness	EN 20105-B02 ≥ level 6	≥ level 6
Chemical resistance	EN 423 good resistance	good resistance
Colours	6	10
Form of delivery	EN 426 Sheet (rolls) 23 r m x 200 cm EN 427 Tiles (box) 30 x 30 cm 68 tiles / box = 6.12 m ²	23 r m x 200 cm 61 x 61 cm 14 tiles / box = 5.21 m ²



All colours also available as tiles.

Please contact your nearest Tarkett Sommer office for delivery details.

Tarkett Sommer's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett Sommer at the address shown for these instructions.

Tarkett Sommer Limited, Century House, Bridgwater Road,
Worcester, WR4 9FA, UK – Tel: 01905 342700 – Fax: 01905 342777
• Tarkett Sommer Australia Pty. Ltd., 16 Anella Avenue, Castle Hill,
N.S.W. 2154 – Tel: (02) 9634 7373 – Fax: (02) 9899 2314 • Tarkett
Sommer Representative Office, 10/F., Easey Commercial Building,
253 Hennessy Road, Wanchai, Hong Kong – Tel: (852) 2877 7588 –
Fax: (852) 2877 7029 • Tarkett Sommer Far East, 5 Lor Bakar Batu
#05-02, Singapore 348 742 – Tel: 7435384 – Fax: 2849336 •
Tarkett Sommer Middle East, Gefinor Center # D206, P O Box 113-
6407 Hamra, Beirut, Lebanon – Tel: 1-752363/4 – Fax: 1-752365 •
Jacobsen Creative Surfaces Ltd, P O Box 28042, Remuera,
Auckland, New Zealand – Tel: 0-9-524 1475 – Fax: 0-9-524 8936 •
Tarkett Sommer International GmbH, Nachtweideweg 1-7, D-67227
Frankenthal, Germany – Tel: Int. +49 6233 811302 – Fax: Int. +49
6233 811620 • Tarkett Sommer AB, S-372 81 Ronneby, Sweden –
Tel: Int. +46-457-710 00 – Fax: Int. +46-457-705 28, 710 20.

www.tarkett-sommer.com



Tarkett Sommer



Homogeneous vinyl flooring



Universal
Modern colours
Reliable



Tarkett Sommer